

AUTOMATIC AIR VENT

PN16 F9516
PN25 F9525



FEATURES & SPECIFICATIONS

- Anti corrosion treatment for internal parts to prevent from the valve rusting
- Large venting capacity
- Air tight
- Available in 15, 20 & 25mm inlet diameter threaded BSPT




PRESSURE & TEMPERATURE RATINGS

Working Pressure	16bar	25bar
Testing Pressure (x1.5)	24bar	37.5bar
Working Temperature	-10°C ... 120°C	
Suitable Media	Water	

MATERIAL SPECIFICATIONS

Part	Material	Specification
Body	Cast Iron	EN-JL 1040
	Ductile Iron	EN-JS 1050
Cover	Cast Iron	EN-JL 1040
	Ductile Iron	EN-JS 1050
Lever	Stainless Steel 304	EN 10088-3 1.4301
Seat Ring	Stainless Steel 304	EN 10088-3 1.4301
Float	Stainless Steel 304	EN 10088-3 1.4301
Float Arm	Stainless Steel 304	EN 10088-3 1.4301
Orifice Button	FPM (Viton)	Commercial

Note : PN25 only available for Ductile Iron body.



DIMENSIONS

DN		Inlet	Outlet	Orifice	D	H
mm	inch					
15	1/2	15	15	1.6	125	145
20	3/4	20	15	1.6	125	145
25	1	25	15	1.6	125	145

INSTALLATION GUIDE

1. Air vent shall be installed vertically with allowance of within 5" from the horizontal pipe line.
2. A ball valve shall be installed at the inlet for maintenance and servicing.
3. Copper tube to be connected from the outlet of the air vent up to drainage ditch.

Fivalco® is Registered Trade Mark
FIVALCO LIMITED
info@fivalco.com | www.fivalco.com

Exclusive Distributor :
ENVALCO SDN. BHD. (1039097-M)
No. 30, Jalan PJU 3/46, Sunway Damansara Technology Park, 47810 Petaling Jaya, Selangor Darul Ehsan, Malaysia
T: 603 - 7883 0018 | F: 603 - 7883 0012 | E: enquiry@envalco.com.my | W: www.envalco.com.my

Fivalco reserves the right to alter the information in this document without prior notice. Fivalco shall not be liable for technical errors or omissions contained herein.